

Operator  
Telephone  
Fax  
e-Mail

## Casablanca Leuchten GmbH FO41-LD61A Casablanca FOLLOX 45 cm high-voltage-LED / UGR-Table

Luminaire: Casablanca Leuchten GmbH FO41-LD61A Casablanca FOLLOX 45 cm high-voltage-LED  
Lamps: 1 x LED

<b>Glare Evaluation According to UGR</b>											
$\rho$ Ceiling		70	70	50	50	30	70	70	50	50	30
$\rho$ Walls		50	30	50	30	30	50	30	50	30	30
$\rho$ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X      Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	22.4	23.7	22.7	23.9	24.1	23.0	24.3	23.3	24.5	24.8
	3H	23.8	24.9	24.1	25.2	25.5	24.5	25.7	24.9	26.0	26.2
	4H	24.3	25.4	24.6	25.6	25.9	25.1	26.2	25.5	26.5	26.8
	6H	24.6	25.6	25.0	25.9	26.2	25.5	26.5	25.9	26.8	27.1
	8H	24.7	25.7	25.1	26.0	26.3	25.6	26.6	26.0	26.9	27.2
	12H	24.7	25.7	25.1	26.0	26.3	25.6	26.6	26.0	26.9	27.2
4H	2H	23.1	24.2	23.4	24.5	24.8	23.6	24.7	23.9	25.0	25.3
	3H	24.7	25.6	25.0	25.9	26.2	25.3	26.2	25.7	26.6	26.9
	4H	25.3	26.1	25.7	26.4	26.8	26.0	26.8	26.4	27.2	27.6
	6H	25.7	26.4	26.1	26.8	27.2	26.5	27.2	26.9	27.6	28.0
	8H	25.8	26.5	26.3	26.9	27.3	26.6	27.3	27.1	27.7	28.1
	12H	25.9	26.5	26.4	26.9	27.4	26.7	27.3	27.2	27.7	28.1
8H	4H	25.6	26.2	26.0	26.6	27.0	26.2	26.9	26.7	27.3	27.7
	6H	26.1	26.6	26.6	27.1	27.5	26.8	27.4	27.3	27.8	28.3
	8H	26.3	26.8	26.8	27.2	27.7	27.0	27.5	27.5	27.9	28.4
	12H	26.4	26.8	26.9	27.3	27.8	27.1	27.5	27.6	28.0	28.5
12H	4H	25.6	26.2	26.0	26.6	27.0	26.2	26.8	26.7	27.2	27.7
	6H	26.2	26.6	26.6	27.1	27.6	26.9	27.3	27.3	27.8	28.3
	8H	26.4	26.8	26.9	27.2	27.7	27.1	27.5	27.6	27.9	28.4
Variation of the observer position for the luminaire distances S											
S = 1.0H		+0.1 / -0.2					+0.1 / -0.1				
S = 1.5H		+0.3 / -0.5					+0.2 / -0.4				
S = 2.0H		+0.4 / -0.8					+0.4 / -0.7				
Standard table		BK05					BK05				
Correction Summand		8.9					9.6				
Corrected Glare Indices referring to 636lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.