

OliNo Energy BV

Operator Marcel van der Steen
 Telephone
 Fax
 e-Mail marcel@olino.org

TDE-Lighttech Cursa 2700K 16 graden / UGR-Table

Luminaire: TDE-Lighttech Cursa 2700K 16 graden
 Lamps: 1 x LED

Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	10.4	11.0	10.6	11.2	11.4	10.4	11.0	10.6	11.2	11.4
	3H	10.3	10.9	10.6	11.1	11.4	10.3	10.9	10.6	11.1	11.4
	4H	10.2	10.8	10.5	11.1	11.3	10.2	10.8	10.5	11.1	11.3
	6H	10.2	10.7	10.5	11.0	11.3	10.2	10.7	10.5	11.0	11.3
	8H	10.1	10.7	10.5	10.9	11.2	10.1	10.7	10.5	10.9	11.2
	12H	10.1	10.6	10.5	10.9	11.2	10.1	10.6	10.5	10.9	11.2
4H	2H	10.3	10.9	10.6	11.1	11.4	10.3	10.9	10.6	11.1	11.4
	3H	10.2	10.7	10.6	11.0	11.3	10.2	10.7	10.6	11.0	11.3
	4H	10.1	10.6	10.5	10.9	11.2	10.1	10.6	10.5	10.9	11.2
	6H	10.1	10.4	10.5	10.8	11.2	10.1	10.4	10.5	10.8	11.2
	8H	10.1	10.4	10.5	10.7	11.1	10.1	10.4	10.5	10.7	11.1
	12H	10.0	10.3	10.5	10.7	11.1	10.0	10.3	10.5	10.7	11.1
8H	4H	10.0	10.3	10.5	10.7	11.1	10.0	10.3	10.5	10.7	11.1
	6H	10.0	10.2	10.4	10.6	11.1	10.0	10.2	10.4	10.6	11.1
	8H	10.0	10.1	10.4	10.6	11.1	10.0	10.1	10.4	10.6	11.1
	12H	9.9	10.1	10.4	10.6	11.0	9.9	10.1	10.4	10.6	11.0
12H	4H	10.0	10.3	10.4	10.7	11.1	10.0	10.3	10.4	10.7	11.1
	6H	9.9	10.1	10.4	10.6	11.0	9.9	10.1	10.4	10.6	11.0
	8H	9.9	10.1	10.4	10.5	11.0	9.9	10.1	10.4	10.5	11.0
Variation of the observer position for the luminaire distances S											
S = 1.0H	+2.6 / -3.8					+2.6 / -3.8					
S = 1.5H	+4.9 / -9.7					+4.9 / -9.7					
S = 2.0H	+6.9 / -14.6					+6.9 / -14.6					
Standard table	BK00					BK00					
Correction Summand	1.0					1.0					
Corrected Glare Indices referring to 392lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 1.00.