

Operator
Telephone
Fax
e-Mail

Taglumo Lighting LEDframe 56 – 2, 4000K / UGR-Table

Luminaire: Taglumo Lighting LEDframe 56 – 2, 4000K
Lamps: 1 x LED

Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	13.7	15.1	14.0	15.3	15.5	13.7	15.1	14.0	15.3	15.5
	3H	15.3	16.5	15.6	16.8	17.1	15.3	16.5	15.6	16.8	17.1
	4H	16.0	17.1	16.3	17.4	17.7	16.0	17.1	16.3	17.4	17.7
	6H	16.4	17.5	16.8	17.8	18.1	16.4	17.5	16.8	17.8	18.1
	8H	16.6	17.6	16.9	17.9	18.2	16.6	17.6	16.9	17.9	18.2
	12H	16.7	17.6	17.0	18.0	18.3	16.7	17.6	17.0	18.0	18.3
4H	2H	14.4	15.6	14.8	15.8	16.1	14.4	15.6	14.8	15.8	16.1
	3H	16.2	17.2	16.6	17.5	17.8	16.2	17.2	16.6	17.5	17.8
	4H	17.0	17.8	17.4	18.2	18.5	17.0	17.8	17.4	18.2	18.5
	6H	17.6	18.3	18.0	18.7	19.1	17.6	18.3	18.0	18.7	19.1
	8H	17.8	18.5	18.2	18.8	19.3	17.8	18.5	18.2	18.8	19.3
	12H	17.9	18.5	18.3	18.9	19.4	17.9	18.5	18.3	18.9	19.4
8H	4H	17.3	18.0	17.7	18.4	18.8	17.3	18.0	17.7	18.4	18.8
	6H	18.0	18.6	18.5	19.0	19.5	18.0	18.6	18.5	19.0	19.5
	8H	18.3	18.8	18.8	19.2	19.7	18.3	18.8	18.8	19.2	19.7
	12H	18.5	18.9	19.0	19.4	19.9	18.5	18.9	19.0	19.4	19.9
12H	4H	17.3	17.9	17.8	18.3	18.8	17.3	17.9	17.8	18.3	18.8
	6H	18.1	18.6	18.6	19.0	19.5	18.1	18.6	18.6	19.0	19.5
	8H	18.4	18.8	18.9	19.3	19.8	18.4	18.8	18.9	19.3	19.8
Variation of the observer position for the luminaire distances S											
S = 1.0H	+0.1 / -0.1					+0.1 / -0.1					
S = 1.5H	+0.2 / -0.3					+0.2 / -0.3					
S = 2.0H	+0.4 / -0.6					+0.4 / -0.6					
Standard table	BK06					BK06					
Correction Summand	1.1					1.1					
Corrected Glare Indices referring to 445lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.