

Operator
Telephone
Fax
e-Mail

DMLUX Verlichtingsarmaturen DM720949-NT Triton LED Downlight 16W/840 1740lm 145x60mm / UGR-Table

Luminaire: DMLUX Verlichtingsarmaturen DM720949-NT Triton LED Downlight 16W/840 1740lm 145x60mm
Lamps: 1 x LED

Glare Evaluation According to UGR											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	25.1	26.1	25.4	26.3	26.6	25.1	26.1	25.4	26.3	26.6
	3H	25.8	26.7	26.1	26.9	27.2	25.8	26.7	26.1	26.9	27.2
	4H	26.0	26.9	26.3	27.1	27.4	26.0	26.9	26.3	27.1	27.4
	6H	26.2	27.0	26.5	27.3	27.6	26.2	27.0	26.5	27.3	27.6
	8H	26.2	27.0	26.6	27.3	27.6	26.2	27.0	26.6	27.3	27.6
	12H	26.2	27.0	26.6	27.3	27.6	26.2	27.0	26.6	27.3	27.6
4H	2H	25.4	26.3	25.7	26.6	26.8	25.4	26.3	25.7	26.6	26.8
	3H	26.2	27.0	26.6	27.3	27.6	26.2	27.0	26.6	27.3	27.6
	4H	26.6	27.2	27.0	27.6	27.9	26.6	27.2	27.0	27.6	27.9
	6H	26.8	27.4	27.2	27.8	28.2	26.8	27.4	27.2	27.8	28.2
	8H	26.9	27.4	27.3	27.8	28.2	26.9	27.4	27.3	27.8	28.2
	12H	27.0	27.4	27.4	27.8	28.3	27.0	27.4	27.4	27.8	28.3
8H	4H	26.7	27.2	27.1	27.6	28.0	26.7	27.2	27.1	27.6	28.0
	6H	27.0	27.4	27.5	27.9	28.3	27.0	27.4	27.5	27.9	28.3
	8H	27.2	27.5	27.6	28.0	28.4	27.2	27.5	27.6	28.0	28.4
	12H	27.2	27.6	27.7	28.0	28.5	27.2	27.6	27.7	28.0	28.5
12H	4H	26.7	27.1	27.1	27.5	28.0	26.7	27.1	27.1	27.5	28.0
	6H	27.1	27.4	27.5	27.9	28.3	27.1	27.4	27.5	27.9	28.3
	8H	27.2	27.5	27.7	28.0	28.5	27.2	27.5	27.7	28.0	28.5
Variation of the observer position for the luminaire distances S											
S = 1.0H		+0.3 / -0.5					+0.3 / -0.5				
S = 1.5H		+0.6 / -1.1					+0.6 / -1.1				
S = 2.0H		+1.4 / -1.8					+1.4 / -1.8				
Standard table		BK03					BK03				
Correction Summand		9.3					9.3				
Corrected Glare Indices referring to 1740lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.