

Operator
Telephone
Fax
e-Mail

Abalight Panel STEP 14501 driver LCI-35W-700mA-TEC-SR / UGR-Table

Luminaire: Abalight Panel STEP 14501 driver LCI-35W-700mA-TEC-SR
Lamps: 1 x LED

Glare Evaluation According to UGR											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	16.5	17.9	16.8	18.1	18.4	16.5	17.9	16.8	18.1	18.4
	3H	18.2	19.5	18.6	19.7	20.0	18.2	19.5	18.6	19.7	20.0
	4H	19.0	20.1	19.3	20.4	20.7	19.0	20.1	19.3	20.4	20.7
	6H	19.6	20.6	19.9	21.0	21.3	19.6	20.6	19.9	21.0	21.3
	8H	19.8	20.8	20.2	21.1	21.5	19.8	20.8	20.2	21.1	21.5
	12H	20.0	21.0	20.3	21.3	21.6	20.0	21.0	20.3	21.3	21.6
4H	2H	17.3	18.4	17.6	18.7	19.0	17.3	18.4	17.6	18.7	19.0
	3H	19.2	20.2	19.5	20.5	20.8	19.2	20.2	19.5	20.5	20.8
	4H	20.0	20.9	20.4	21.3	21.6	20.0	20.9	20.4	21.3	21.6
	6H	20.8	21.6	21.2	21.9	22.3	20.8	21.6	21.2	21.9	22.3
	8H	21.1	21.8	21.5	22.2	22.6	21.1	21.8	21.5	22.2	22.6
	12H	21.3	21.9	21.7	22.4	22.8	21.3	21.9	21.7	22.4	22.8
8H	4H	20.4	21.1	20.8	21.5	21.9	20.4	21.1	20.8	21.5	21.9
	6H	21.3	21.9	21.8	22.3	22.8	21.3	21.9	21.8	22.3	22.8
	8H	21.7	22.2	22.2	22.7	23.1	21.7	22.2	22.2	22.7	23.1
	12H	22.0	22.5	22.5	22.9	23.4	22.0	22.5	22.5	22.9	23.4
12H	4H	20.4	21.1	20.9	21.5	21.9	20.4	21.1	20.9	21.5	21.9
	6H	21.4	21.9	21.9	22.4	22.8	21.4	21.9	21.9	22.4	22.8
	8H	21.8	22.3	22.3	22.8	23.3	21.8	22.3	22.3	22.8	23.3
Variation of the observer position for the luminaire distances S											
S = 1.0H		+0.1 / -0.1					+0.1 / -0.1				
S = 1.5H		+0.2 / -0.3					+0.2 / -0.3				
S = 2.0H		+0.3 / -0.6					+0.3 / -0.6				
Standard table		BK07					BK07				
Correction Summand		4.8					4.8				
Corrected Glare Indices referring to 3180lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.