

Operator  
Telephone  
Fax  
e-Mail

## DMLUX Verlichtingsarmaturen Manto3 LED Paneel 120x30cm 4000K / UGR-Table

Luminaire: DMLUX Verlichtingsarmaturen Manto3 LED Paneel 120x30cm 4000K  
Lamps: 1 x LED

<b>Glare Evaluation According to UGR</b>											
$\rho$ Ceiling	70	70	50	50	30	70	70	50	50	30	
$\rho$ Walls	50	30	50	30	30	50	30	50	30	30	
$\rho$ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	18.0	19.4	18.3	19.6	19.8	18.0	19.4	18.3	19.6	19.8
	3H	19.6	20.9	20.0	21.1	21.4	19.6	20.9	20.0	21.1	21.4
	4H	20.3	21.5	20.6	21.7	22.0	20.3	21.5	20.6	21.7	22.0
	6H	20.8	21.9	21.2	22.2	22.5	20.8	21.9	21.2	22.2	22.5
	8H	21.0	22.0	21.3	22.3	22.6	21.0	22.0	21.3	22.3	22.6
	12H	21.1	22.1	21.5	22.4	22.7	21.1	22.1	21.5	22.4	22.7
4H	2H	18.7	19.9	19.1	20.2	20.5	18.7	19.9	19.1	20.2	20.5
	3H	20.5	21.5	20.9	21.8	22.2	20.5	21.5	20.9	21.8	22.2
	4H	21.3	22.2	21.7	22.6	22.9	21.3	22.2	21.7	22.6	22.9
	6H	22.0	22.7	22.4	23.1	23.5	22.0	22.7	22.4	23.1	23.5
	8H	22.2	22.9	22.6	23.3	23.7	22.2	22.9	22.6	23.3	23.7
	12H	22.3	23.0	22.8	23.4	23.8	22.3	23.0	22.8	23.4	23.8
8H	4H	21.7	22.4	22.1	22.8	23.2	21.7	22.4	22.1	22.8	23.2
	6H	22.4	23.0	22.9	23.4	23.9	22.4	23.0	22.9	23.4	23.9
	8H	22.8	23.3	23.2	23.7	24.2	22.8	23.3	23.2	23.7	24.2
	12H	23.0	23.4	23.5	23.9	24.4	23.0	23.4	23.5	23.9	24.4
12H	4H	21.7	22.3	22.1	22.7	23.2	21.7	22.3	22.1	22.7	23.2
	6H	22.5	23.0	23.0	23.5	23.9	22.5	23.0	23.0	23.5	23.9
	8H	22.9	23.3	23.4	23.8	24.3	22.9	23.3	23.4	23.8	24.3
Variation of the observer position for the luminaire distances S											
S = 1.0H	+0.1 / -0.1					+0.1 / -0.1					
S = 1.5H	+0.2 / -0.3					+0.2 / -0.3					
S = 2.0H	+0.4 / -0.6					+0.4 / -0.6					
Standard table	BK06					BK06					
Correction Summand	5.5					5.5					
Corrected Glare Indices referring to 4277lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.