

Operator
Telephone
Fax
e-Mail

abalight 14514 + 19035 LED-Panel STEP II Art.-Nr. 14514 bei 900 mA / UGR-Table

Luminaire: abalight 14514 + 19035 LED-Panel STEP II Art.-Nr. 14514 bei 900 mA
Lamps: 1 x LED

Glare Evaluation According to UGR											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	15.9	17.1	16.2	17.3	17.5	15.9	17.1	16.2	17.3	17.5
	3H	17.0	18.0	17.3	18.3	18.5	17.0	18.0	17.3	18.3	18.5
	4H	17.4	18.4	17.7	18.7	18.9	17.4	18.4	17.7	18.7	18.9
	6H	17.8	18.7	18.1	19.0	19.3	17.8	18.7	18.1	19.0	19.3
	8H	17.9	18.8	18.3	19.1	19.4	17.9	18.8	18.3	19.1	19.4
	12H	18.0	18.8	18.4	19.2	19.5	18.0	18.8	18.4	19.2	19.5
4H	2H	16.4	17.3	16.7	17.6	17.9	16.4	17.3	16.7	17.6	17.9
	3H	17.6	18.5	18.0	18.8	19.1	17.6	18.5	18.0	18.8	19.1
	4H	18.2	18.9	18.6	19.3	19.6	18.2	18.9	18.6	19.3	19.6
	6H	18.7	19.3	19.1	19.7	20.1	18.7	19.3	19.1	19.7	20.1
	8H	18.9	19.5	19.3	19.9	20.3	18.9	19.5	19.3	19.9	20.3
	12H	19.0	19.6	19.5	20.0	20.4	19.0	19.6	19.5	20.0	20.4
8H	4H	18.4	19.0	18.9	19.4	19.8	18.4	19.0	18.9	19.4	19.8
	6H	19.1	19.5	19.5	20.0	20.4	19.1	19.5	19.5	20.0	20.4
	8H	19.3	19.8	19.8	20.2	20.7	19.3	19.8	19.8	20.2	20.7
	12H	19.6	19.9	20.1	20.4	20.9	19.6	19.9	20.1	20.4	20.9
12H	4H	18.4	19.0	18.9	19.4	19.8	18.4	19.0	18.9	19.4	19.8
	6H	19.1	19.5	19.6	20.0	20.5	19.1	19.5	19.6	20.0	20.5
	8H	19.4	19.8	19.9	20.3	20.8	19.4	19.8	19.9	20.3	20.8
Variation of the observer position for the luminaire distances S											
S = 1.0H		+0.2 / -0.2					+0.2 / -0.2				
S = 1.5H		+0.4 / -0.7					+0.4 / -0.7				
S = 2.0H		+0.7 / -1.0					+0.7 / -1.0				
Standard table		BK05					BK05				
Correction Summand		1.9					1.9				
Corrected Glare Indices referring to 4039lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.